

WATER AND WASTEWATER MANAGEMENT FOR SUSTAINABLE VITICULTURE AND OENOLOGY IN SOUTH PORTUGAL – A REVIEW

GESTÃO DA ÁGUA E DAS ÁGUAS RESIDUAIS PARA UMA VITICULTURA E ENOLOGIA SUSTENTÁVEIS NO SUL DE PORTUGAL – REVISÃO

Joaquim M. Costa^{1*}, Margarida Oliveira^{1,2}, Ricardo J. Egipto³, João F. Cid¹, Rita A. Fragoso¹,
Carlos M. Lopes¹, Elisabeth N. Duarte¹

¹ Centro de Investigação em Agronomia, Alimentos, Ambiente e Paisagem (LEAF), Instituto Superior de Agronomia, Universidade de Lisboa, Tapada da Ajuda, 1349-017 Lisboa, Portugal.

² ESAS, UIHPS, Instituto Politécnico de Santarém, Quinta do Galinheiro, S. Pedro, 2001-904 Santarém, Portugal.

³ INIAV I.P., Instituto Nacional de Investigação Agrária e Veterinária, Quinta da Almoíña, 2565-191, Dois Portos, Portugal.

*corresponding author: Tel.: +351 21 365 32 95, e-mail: miguelcosta@isa.ulisboa.pt

(Received 13.09.2019. Accepted 31.01.2020)

SUMMARY

Assessing sustainability of the wine industry requires improved characterization of its environmental impacts, namely in terms of water use. Therefore, quantification of water inputs and wastewater (WW) outputs is needed to highlight inefficiencies in wine production and related consequences for the environment. Water use and WW generation in irrigated viticulture and oenology remains insufficiently quantified for dry Mediterranean regions (e.g. South Portugal). This paper is focused on wine production under warm and dry climate conditions in the winegrowing region of Alentejo (South Portugal). This region experiences increasingly dry conditions, while the irrigated area keeps expanding, which puts exacerbates the pressure on existing local and regional water resources. Additionally, more erratic variation in climate conditions and the tendency for increasingly extreme climate events (e.g. heat waves) pose more challenges to Alentejo's wine sector. We conclude that quantitative information on water use and management is not always easy to obtain or access, which hinders improved strategies and/or policies for water use at farm, winery and region-level. Up-to-date statistics and robust metrics can help to better characterize water use and WW flows for Alentejo's wine region, while optimizing management in vineyards and wineries, in companies and region-wide. The paper is focused on a "Farm-Winery" scenario, which is the most common in South Portugal's wine sector.

RESUMO

A avaliação da sustentabilidade da indústria vitivinícola requer uma caracterização detalhada do seu impacto ambiental, nomeadamente ao nível do factor água. A quantificação detalhada dos consumos de água e das águas residuais produzidas (WW) é crucial para identificação de ineficiências na indústria da vinha e do vinho. A utilização da água e a gestão dos efluentes em viticultura regada e na adegas permanecem pouco quantificados nas regiões mediterrânicas. O presente trabalho centra-se na produção de vinho em condições de clima quente e seco, tomando como exemplo a região vitivinícola do Alentejo (Sul de Portugal). A região está sujeita a situações de seca mais frequentes e severas, enquanto a área regada continua em expansão, o que pressiona os recursos hídricos locais e regionais. Além disso, as condições climáticas altamente variáveis e a maior tendência para eventos climáticos extremos (e.g. ondas de calor) colocam desafios ao setor vitivinícola no Sul de Portugal. Concluímos que a informação quantitativa relativa ao uso e gestão de água não está sempre facilmente disponível, limitando a otimização de estratégias e/ou políticas para o uso da água ao nível da vinha, da adegas e da região. Dados atualizados e indicadores robustos podem ajudar a caracterizar melhor o uso de água e a geração de água residual na região vitivinícola do Alentejo, otimizando a gestão na vinha e na adegas, ao nível da empresa e da região. O artigo centra-se num cenário de produtor-engarrafador ("Farm-Winery"), que é o mais comum no setor vitivinícola no Sul de Portugal.

Key words: Irrigated viticulture, sustainable water use, water metrics, water scarcity, wastewater reuse.

Palavras-chave: Escassez de água, métricas de água, reutilização de águas residuais, uso sustentável da água, viticultura regada.

INTRODUCTION

Water use in viticulture and oenology demands improved quantification to support present and future adaptation strategies of the wine industry to climate

change, while increasing water use efficiency and minimizing environmental burdens (Chiusano *et al.*, 2015; Costa *et al.*, 2016; Martins *et al.*, 2018). The challenges posed to the wine industry extend to wastewater (WW) generation and management in

both viticulture and oenology phases (Castex *et al.*, 2015; Peth *et al.*, 2017). This is particularly important for Mediterranean regions, characterized by hot dry summers and mild winters, and increasingly exposed to extreme climate events (Fraga *et al.*, 2018; Lopes *et al.*, 2018).

Portugal is a typical Mediterranean wine producer, with around 191,000 ha of vineyards and a wine production of about 6.5 MhL in 2017 (IVV, 2018). It is the 11th largest producer worldwide and the 9th largest amongst global wine exporters (OIV, 2018).

The wine-producing region of Alentejo (South Portugal) is one of 14 Portuguese wine regions. It has a total vineyard area of 23,879 ha and accounts for approximately 12.5% of the country's total wine grape production area (IVV, 2018). Most of the Alentejo region has a Csa climate, according to the Köppen-Geiger updated classification (Peel *et al.*, 2007), characterized by warm and dry summers (IPMA, 2017). Precipitation is very low or absent in summer and air vapour pressure deficit (VPD_{air}) can

be extremely high (up to 8 kPa), generating high crop evapotranspiration losses (COTR-ATEVA, 2009; Barroso *et al.*, 2017). Bioclimatic indices such as the Dryness Index (DI) (Riou *et al.*, 1994), which help to assess regional suitability for wine production and predict climatic impact on viticulture, show a tendency for increasingly severe drought conditions in Alentejo (Figure 1) (Fraga *et al.*, 2018; Lopes *et al.*, 2018). This is in line with the fact that the region is experiencing more frequent heat waves, which poses increasing risks to the sector (Lopes *et al.*, 2018; Silvestre *et al.*, 2018). In this context, irrigation emerged as a major tool to overcome the constraints posed by adverse climate conditions and support risk management, *e.g.* due to heat waves (Silvestre *et al.*, 2018). Consequently, the total irrigated vineyard area in Alentejo is nowadays largely above 10,000 ha (more than 50% of total surface) (Costa *et al.*, 2019). This was a fast increment, if we consider that in 2002 there were only 4,600 ha with irrigated vineyards (CVRA, 2002), and the trend should remain, supported by the Alqueva dam (EDIA, 2018).




Figure 1. Ten-years interval variability of the Dryness Index (DI, mm) (Riou *et al.*, 1994), for (a) Portalegre, (b) Évora and (c) Beja (Alentejo region, South Portugal) using datasets from local weather stations. $DI = Wo + P - Tv - Es$, where Wo is the soil water reserve at April 1 (assumed as 200 mm); P is the accumulated precipitation (mm); Tv is the vineyard's potential transpiration (mm); Es is the soil water loss by evaporation (mm). The DI estimates soil water availability taking into account vine's transpiration, soil evaporation and precipitation between April 1 and September 30 (in the Northern Hemisphere). The box-plots are bounded on top by the 3rd quartile ($Q3$), on the bottom by the 1st quartile ($Q1$) and divided by the median ($Q2$). The average value of the series is represented by (x) and (o) indicates the DI values. The top whisker is defined as $Q3 + 1.5 \times IQR$ and the lower whisker as $Q1 - 1.5 \times IQR$, where $IQR = Q3 - Q1$.

Variabilidade observada para um período de dez anos do Índice de Secura (DI) (Riou *et al.*, 1994), para a região de (a) Portalegre, (b) Évora e (c) Beja (região do Alentejo, Sul de Portugal). $DI = Wo + P - Tv - Es$, onde Wo é a reserva de água do solo a 1 de Abril (assumido como 200 mm); P é a precipitação acumulada (mm); Tv é a transpiração potencial da vinha (mm); Es é a perda de água no solo por evaporação (mm). O DI estima a disponibilidade hídrica do solo considerando a transpiração da videira, evaporação do solo e precipitação ocorridas entre 1 de abril e 30 de setembro (no Hemisfério Norte). A caixa de bigodes é delimitada no seu topo superior pelo terceiro quartil ($Q3$), na parte inferior pelo primeiro quartil ($Q1$) e dividida pelo valor da mediana ($Q2$). O valor médio da série é representado por (x) e (o) indica os diferentes valores de DI. A barreira superior é definida como $Q3 + 1.5 \times IQR$ e a barreira inferior é definida como $Q1 - 1.5 \times IQR$, onde $IQR = Q3 - Q1$.

Water accounting in irrigated agriculture is often characterized by poor metrics and scarce data reporting (Corbo *et al.*, 2014; Santiago-Brown *et al.*, 2015; Liu *et al.*, 2017; Pfister *et al.*, 2017; EU

Commission, 2017). In addition, indicators to assess the sustainability of the wine industry vary between regions and countries, making it difficult to compare “companies/farms” performance (Santini *et al.*, 2013;

Corbo *et al.*, 2014; Oliveira *et al.*, 2019). In Portugal, recent efforts in the wine sector to improve its environmental sustainability are reported in several studies (Neto *et al.*, 2013; Quinteiro *et al.*, 2014; Engel *et al.*, 2015; CVRA, 2016), but information remains scarce. In addition, auditing for environmental performance demands more precise water use monitoring in farms and wineries, as well as data on wastewater production and/or quality (EPA, 2004). In parallel, more homogeneous standards/metrics for sustainability, independently of the *terroir* are on demand (Costa *et al.*, 2016; Oliveira *et al.*, 2019).

Therefore, the major aims of this review are to point out the risks of increasingly dry conditions for irrigated viticulture and oenology in South Portugal, while emphasizing the role(s) of improved water metrics for more efficient water use and WW management in the vineyard and in the winery.

WATER USE AND WASTEWATER PRODUCTION IN VINEYARDS AND WINERIES

A strategic approach towards more sustainable water use in dry regions' wine production must involve the combined assessment of water needs and WW production/management in both vineyards and wineries. This is highly relevant for Mediterranean regions, *e.g.* South Portugal, where values of 88 to 264 L of water can be spent per liter of wine produced (Engel *et al.*, 2015). More recent literature points to even higher values of annual water footprint, reaching 360 L per 0.75 L bottle (450 L per liter of wine), as referred by Saraiva *et al.* (2019) for South Portugal wines. The Portuguese wine industry is based on small to medium size vineyards and small wineries, with 98% of them having production volumes below 2000 hL (IVV, 2016). Therefore, a "Farm-Winery" approach, in which vineyards and wineries are considered in a single stream grape system, will represent the majority of Portuguese viticulture and oenology stakeholders and can be used to support the analysis of water use and management in the Portuguese vine and wine sector (Oliveira *et al.*, 2019).

Water use and wastewater production issues in the vineyard

In dry areas, viticulture accounts for the highest fraction of water used in wine production, reaching values comprised between 70 to almost 90% of total water use in some cases (Ene *et al.*, 2013; Correia,

2015; Saraiva *et al.*, 2019). Despite grapevine being considered well-adapted to dry conditions, irrigated cultivation uses a considerable water volume per season under Mediterranean conditions (EDIA, 2018; Table I).

Water use in the vineyard depends on several factors: 1) Plant – canopy leaf area and canopy gas exchanges, stem and root morphology, plant hydraulics, phenology, genotype; 2) Soil – depth, texture, organic matter content, water availability, soil temperature (T_s); 3) Atmospheric conditions – rainfall (R), air vapor pressure deficit (VPD_{air}), air temperature (T_{air}), wind speed (W_s); 4) Agronomic choices and practices – soil preparation, plant density, rootstock/variety combination, row orientation, floor management, training system, canopy management (Figure 2).

In the Alentejo wine region, irrigation needs are expected to vary between 2,500-3,000 m³/ha per year for an average production of 7.5 to 10 t/ha (EDIA, 2018). Nevertheless, these indicative values are 30-50% higher than the ones observed under deficit irrigation, which is already being implemented in commercial vineyards in the region for some years (see Table I).

More sustainable grapevine irrigation should supply enough water, at the right moment, to guarantee a profitable yield and winemakers' desired berry composition without compromising vine longevity. Deficit irrigation strategies should be based on a precise monitoring of atmospheric conditions, soil water content and plant water status. In addition, Alentejo has a wide annual climate variability (see Figure 1 and Table I), with increasingly drier winters and warmer temperatures in recent years, which pose additional risks to the wine sector in the region. Even though the degree of corporatization has been increasing in the region, and with it the adoption of better management strategies (INE, 2013; 2016), there is still a large variation among farms regarding irrigation efficiency, with timing and volume of irrigation being decided mostly through experience and observation, instead of atmosphere/crop/soil monitoring and precise water metrics (COTR-ATEVA, 2009; Levidow *et al.*, 2014). Audits to water use in farms and wineries are also not a widely adopted practice (Radke *et al.*, 2015). This suggests that a wider network of simple monitoring sensors, more technical support and broader implementation of sustainability programs for the sector, will be a step forward to optimize water management at company and region level.

Table I

Climate conditions and irrigation water volumes applied under sustained deficit irrigation (SDI) conditions implemented in a field trial at a commercial vineyard in the Alentejo winegrowing region (Reguengos) along three consecutive years (Costa *et al.*, 2019). Average rainfall (mm); Reference Evapotranspiration (ET_o); T_{air} – air temperature; Irrigation volume: water volume applied during the irrigation period; SDI management was based on vine leaf water potential threshold of ~ 0.4 to 0.5 MPa

Clima e volumes de água de rega aplicados ao longo de três anos consecutivos em condições de rega deficitária sustentada (SDI) implementada num ensaio conduzido numa vinha comercial da região do Alentejo (Reguengos) (Costa et al., 2019). Precipitação média (mm); Evapotranspiração de referência (ET_o); T_{air} – temperatura do ar; Volumes de rega: dotação aplicada durante o período de rega. A gestão da rega deficitária foi baseada em limiares na medição do potencial hídrico foliar de base (limiares entre ~ 0.4 a 0.5 MPa).

Year	Mean/ Max T_{air} (Jun - Aug) (°C)	Rainfall during dormancy period (Oct - Feb) (mm)	Rainfall during growth period (Mar - Aug) (mm)	Cumulative ET_o (Mar - Aug) (mm)	SDI irrigation volume (May/Jun - Aug) (mm)
2013	24.5/34.3	308	255	820	111
2014	23.2/32.8	321	157	776	67
2015	24.9/34.6	288	95	940	165




Figure 2. Illustrative diagram showing the main soil-plant-atmosphere water fluxes taking place in an irrigated vineyard with cover crops in the interrow and including the WW fluxes related to the spraying of plant protection products (PPP) – WW_{ppp} . Irrigation can also include fertigation. Evapotranspiration accounts for soil, grass and vines. T_{air} – Air temperature; VPD_{air} – Air vapour pressure deficit; W_s – Wind speed; R_n – Solar Radiation; O.M. – Organic matter;.

Diagrama ilustrando os principais fluxos de água numa vinha regada com enrelvamento na entrelinha, incluindo os fluxos de águas residuais (WW) relacionados com a utilização de pesticidas (“PPP”) – WW_{ppp} . A rega também pode permitir fertilização. Evapotranspiração inclui a componente solo, relvado e videiras. T_{air} – Temperatura do ar; VPD_{air} – Deficit de pressão do vapor do ar; W_s – Velocidade do vento; R_n – Radiação solar; O.M. – Matéria Orgânica.

A much less described item in conventional viticulture is the volume of WW generated in the

vineyard ($WW_{vineyard}$), mainly related to spraying of plant protection products (PPP) and/or improper

disposal/management of PPP residues (Doruchowski *et al.*, 2014; Otto *et al.*, 2015). The WW_{vineyard} may represent a minor percentage of the overall volume of water used in irrigated vineyards, but its impact on soil and groundwater contamination can be significant. For example, Rochard and Codis (2004) indicate that for a volume of 108 to 1400 L of water used per spraying treatment, a total amount of 41 L and 354 L of WW can be generated, respectively. In turn, the volume of clean water used to wash sprayers has been shown to vary between 95 L and 190 L per day of spraying application (IFV, 2010). Such range of variation can be due to technical and operational factors, such as spraying frequency, sprayers' dimension, operators' experience, or cleaning equipment specificities (*e.g.* high pressure cleaning saves about 50% of water relatively to conventional sprayers), but also to the characteristics of the *terroir* (IFV, 2010). The WW volumes derived from washing protective clothing and empty pesticide containers should be accounted as well, but data is often unavailable.

The wine industry is strongly committed to reduce the amount of PPP in viticulture (EIP-AGRI, 2019), namely by adoption of Integrated Crop Management (ICM) and biological control measures and/or novel dosing methods based on dynamic variation of canopy leaf area, phenology and climate conditions (*e.g.* based on modelling software and decision support systems) (Kuflik *et al.*, 2009; Gil *et al.*, 2011, 2014; Pérez-Expósito *et al.*, 2017). For example, it is now possible to optimize the applied volume of PPP as function of canopy area/volume, resulting in a more precise site-specific application, with considerable water savings (Gil *et al.*, 2014; Campos *et al.*, 2019). Nevertheless, this occurs mostly in large-scale operations and companies.

Water use and wastewater production issues in the winery

Water use in the winery is mainly related to cleaning operations – equipment, tanks, vats, barrels, presses, de-stemmers, reception hoods, as well as taps, floors, walls and pipes (Pirra and Bianchi, 2007; Andreattola *et al.*, 2009; Oliveira *et al.*, 2019). Water consumption depends on type and size of the winery, the type of wine produced and the adopted winemaking technology (Andreattola *et al.*, 2009; GWRDC, 2011).

The maximum water consumption in the winery occurs during vintage and in the 1st racking period (Duarte *et al.*, 2004; Oliveira and Duarte, 2016; Oliveira *et al.*, 2019). The WW flows are proportional

to the vintage duration (GWRDC, 2011). Duarte *et al.* (2004) and Oliveira and Duarte (2016) proposed a simpler approach in which two or more activities are combined. They consider two periods: vintage and 1st racking (Period I) – characterized by high peak flows and high pollution loads – and the remaining activities *e.g.* bottling, are encompassed in Period II – characterized by reduced water flows and medium/low pollution loads. The lack of distinction between these two periods may explain the large variation reported in literature for the volumes of water used in wineries (L water/L wine produced) (Table II).

TABLE II

Water consumption/wastewater production in the winery during the winemaking process based on previous literature.

Consumo de água / produção de águas residuais na adegas durante o processo de vinificação, baseados em literatura existente.

Volume water (L) / wine produced (L)	Source
< 1	Andreattola <i>et al.</i> (2009); Rochard and Kerner (2009); Welz <i>et al.</i> (2016).
1-4	Shepherd <i>et al.</i> (2001); Duarte <i>et al.</i> (2004); Vlyssides <i>et al.</i> (2005); Fernández <i>et al.</i> (2007); Stephano <i>et al.</i> (2008); Andreattola <i>et al.</i> (2009); Bolzonella <i>et al.</i> (2010); Lucas <i>et al.</i> (2010); Amienyo <i>et al.</i> (2014); CSWA (2014); Radke <i>et al.</i> (2015); Roman-Sanchez <i>et al.</i> (2015); Oliveira and Duarte (2016); Da Ros <i>et al.</i> (2016); Oliveira <i>et al.</i> , (2019); Esporão (2018).
4-8	Kumar and Kookana (2006); Andreattola <i>et al.</i> (2009); Mosse <i>et al.</i> (2011).
>8	Van Schoor (2005); Kumar and Christen (2009); Andreattola <i>et al.</i> (2009).

Similarly to vineyards, WW production in wineries remains not fully characterized. Data collected in Alentejo shows that 60-86% of the total WW is produced in Period I (Oliveira and Duarte, 2015), which is similar to Italian wineries, where 78% of the WW is generated during vintage and 1st racking (Lofrano *et al.*, 2009). Likewise, WW characteristics need a better assessment, as they depend on the working period and the type of winemaking technologies used.

The winery WW contains grape pulp, skins and seeds (Devesa-Rey *et al.*, 2011; Oliveira and Duarte, 2016). This complex matrix of different flows comprises suspended solids, readily biodegradable compounds (fructose, glucose and ethanol) and other difficult-to-

remove compounds (e.g. surfactants and polyphenols), which may be problematic when directly discharged in treatment system facilities (Oliveira *et al.*, 2009; Mosse *et al.*, 2011; Okada *et al.*, 2013). The organic matter present in WW generally ranges from 1 to 25 g of COD L⁻¹ and depends on the working period (Petrucchioli *et al.*, 2002; Lofrano *et al.*, 2009). Higher organic loads are normally originated in Period I, but high levels of COD can also be recorded in Period II (50 g COD L⁻¹) probably due to inadequate lees removal (Oliveira *et al.*, 2009). In the same way, the biodegradability ratio (BOD₅/COD) of WW depends on the working periods, being higher for the WW generated in Period I (Fernández *et al.*, 2007; Oliveira *et al.*, 2009).

Keeping the complete record of WW flow streams helps winery managers to estimate the required storage and treatment infrastructures, because it depends on the size of the winery, the grape variety and/or the harvest period (Oliveira *et al.*, 2009; Mosse *et al.*, 2011; Welz *et al.*, 2016). Other critical issues for efficient WW management in the wineries are the wide range of pH values in WW, as well as the high dissolved solids content and the presence of indigenous microorganisms, e.g. bacteria and yeast (Eusébio *et al.*, 2005; Mosse *et al.*, 2011).

WATER METRICS AND ENVIRONMENTAL IMPACT ASSESSMENT IN WINE PRODUCTION

Water use indicators for the vineyard and the winery

Water metrics in wine production must rely on robust indicators and methods that assist growers and wine managers in understanding water cycle streams in their farms and wineries, respectively (Christ and Burrit, 2013; Peth *et al.*, 2017). Medrano *et al.* (2015) consider different indicators to evaluate water use efficiency, ranging from leaf eco-physiological level (e.g. Net photosynthesis/Transpiration = Instantaneous Water Use Efficiency) to crop level (Yield/Water use = Crop water use efficiency). In a more practical approach, Skewes (1998) proposed several basic indicators to evaluate water productivity in the vineyard. Skewes (1998) includes the ratio between grape yield and the volume of irrigation water used (t/m³), but also considers the ratio between profit and the volume of water used (profit (€)/water volume (m³)). In addition, and to incorporate the potential environmental impact of the WW_{vineyard}, we may consider as well the volume of WW derived from PPP application (WW_{PPP}), which would be translated into another potential indicator of water

usage/productivity: volume of WW_{PPP} produced per kg of harvested grapes. However, this indicator can have a large variation, due to the inter-annual variability of weather conditions (see Table I) and related pest pressure, as it occurs under Mediterranean conditions.

In the winery, the volume of WW generated per liter of wine produced (WW_{winery}) is a widely adopted metric (Table II). However, calculation of a global indicator for small and small to medium farm-wineries must take into account the type of grape that is processed (e.g. white vs. red), the labour periods (Periods I and II) and the implementation of best available technics (BAT) (see Table III). This allows stakeholders to evaluate WW_{winery} output along different labour periods, for different grape types, production specificities (e.g. kg grapes production/year), vinification rate and annual water consumption in oenological processes, assuming that all water consumed is discharged as wastewater. This approach would support decision making on winery technologies to reach treated wastewater quality requirements.

Water use indicators: limitations and possible applications to Alentejo wine production

The environmental impact of water use by agriculture is usually amplified in dry climates. Wine production in dry areas (e.g. Alentejo - Portugal) can promote water abstraction and/or pollution of surface and/or groundwater due to WW_{PPP} runoff in the field and/or by WW_{winery} mismanagement. Therefore, a set of indicators is needed to support the assessment of environmental impacts of the wine industry, with focus on water and wastewater management. Indicators focused on water stress/water scarcity can support water use monitoring and management at regional and local levels, contributing to assess the impact of agriculture on water availability, consumption and pollution (OECD, 2011; EU Commission, 2012; Moore *et al.*, 2015; Liu *et al.*, 2017; Xu and Wu, 2017). Among these indicators we can consider the Relative Water Stress Index (RWI) (Vörösmarty *et al.*, 2000), also defined as the Water Availability Index (WAI) (EU Commission, 2012), which provides a measure of water demand pressures from domestic, industrial and agriculture sectors in relation to local and upstream water supplies. In turn, the Water Stress Index (WSI; Pfister *et al.* 2009), is a variation of the RWI that incorporates climate variability, which can be relevant for regions such as Alentejo, characterized by a wide inter-annual climate variation (see Figure 1 and Table I).

TABLE III

Global and dedicated indicators for wastewater flows in the winery (WW_{winery}) (Adapted from Duarte *et al.*, 2004; Oliveira e Duarte, 2016 and Oliveira *et al.*, 2019)

Indicadores globais e dedicados para fluxos de água residual tratada em adega (Adaptado de Duarte et al., 2004; Oliveira e Duarte, 2016 e Oliveira et al., 2019).

Indicators	Winery type		
	Small / Medium		
Global	Type of grape	White	Red
	$L_{\text{water}}/L_{\text{wine}}$	1-2	2-3
With BAT *		0.6-0.7	
Dedicated	Period I (30-60 days)	Wastewater ratio (Period I/year)	0.7
	Period II (305-335 days)	Wastewater ratio (Period II/year)	0.3

* BAT implementation leads to 30-40% reduction in water consumption (data not shown).

The use of regional and global indicators could be optimized if combined with other methodologies such as Water Footprint (WFP), or Life Cycle Assessment (LCA), for a more robust analysis of the environmental impact of agricultural production (Brown *et al.*, 2011; Liu *et al.*, 2017). Indeed, the WFP accounts for both direct and indirect use of water by a consumer or producer and it works as a spatial-temporal indicator of freshwater use in agro-food products, including wine (Hoekstra *et al.*, 2011; Ene *et al.*, 2013; Lamastra *et al.*, 2014; Bonamente *et al.*, 2015; Saraiva *et al.*, 2019). However, WFP methodology is not consensual (Perry, 2014) and inconsistencies in underlying used water databases pose concern among researchers (Vanham and Bidoglio, 2013). Nevertheless, Bonamente *et al.* (2015) showed that red wine production in Umbria (Italy) had a WFP of 632 L/bottle (0.75 L), which agrees with the global WFP value proposed by Hoekstra *et al.* (2011). In turn, values presented by Capri (2016) for Italian certified wines (“VIVA Sustainable Wine”) were shown to vary between 530 L/bottle (0.75L), for the Lambrusco variety, up to 1230 L for Sagrantino Montefalco. The major contribution (98.3%) for the WFP relates to green water (rainfall), with a minor contribution of grey water (polluted water) (1.2%) and blue water (0.5%).

Ene *et al.* (2013) described another pattern of WFP for low-yield Romanian vineyards (less than 4 t/ha) of the Iasi County and using multiple varieties (*e.g.* Feteasca alba, Sauvignon, Chardonnay, Riesling). Although the major component is still green water, the distribution of the WFP components was in this case 82% for green water, 15% for grey water and 3% for blue water. Moreover, as WFP values for food products vary with geographic location and climate, these factors must be considered when analysing the wine sector and related wine WFP. Indeed, inter and intra-annual variation of WFP has been observed for several crops including cereals, vegetables and apples (Zhuo *et al.*, 2016). This is an important drawback, as the WFP is only representative for the reported year, while the decision-making process requires long-term and more robust serial historic data, which is not always available (Liu *et al.*, 2017). Under typical Mediterranean climate conditions, WFP values are thus expected to vary with the highly variable rainfall (green water) and irrigation needs (blue water) (*e.g.* 30-100% from year to year). This is in line with Vázquez-Rowe *et al.* (2012), who emphasized the impact of the harvest year when reporting the environmental impact of wine production and the need for including a timeline analysis in the wine sector. To minimize such a variation, the WFP

estimation has been standardized by the ISO norm 14046 (ISO, 2014; Lovarelli *et al.*, 2016). The LCA is another standardized methodology to assess environmental burdens of a product from its production to its disposal or recycling (cradle-to-grave approach) according to the ISO standard 14040 series, (ISO, 2014) and it has been used to characterize the wine supply chain (Neto *et al.*, 2013; Quinteiro *et al.*, 2014). Neto *et al.* (2013) identified four stages of wine production with relevant environmental impact: viticulture, wine production (winemaking to storage), wine distribution and bottle production. Nevertheless, the LCA approach can fail to truly represent environmental impacts related to water and WW management (Comandaru *et al.*, 2012) and an improved temporal resolution (*e.g.* more frequent assessments in time) is needed to attain correct conclusions based on LCA of crop production (Pfister and Bayer, 2014). This must be tested for grape and wine production.

STRATEGIES TO IMPROVE WATER USE AND WASTEWATER MANAGEMENT IN THE VINEYARD AND WINERY

In order to minimize WW production, several strategies can be adopted to save water in the vineyard and in the winery. We further describe different approaches in the context of Mediterranean wine production.

Strategies for the vineyard

Water saving and water protection strategies in the vineyard may include short and long-term approaches. On the short-term, more efficient irrigation practices (*e.g.* deficit irrigation) and more precise irrigation scheduling can minimize the negative impacts of climate change on viticulture in South Mediterranean countries and help to save water (Chaves *et al.*, 2010; Iglesias and Garrote, 2015; Medrano *et al.*, 2015; UN-WATER, 2015) (Table I). Literature reports differences in water use efficiency by different grapevine genotypes, which should be considered for irrigation management purposes (Costa *et al.*, 2016). The use of locally adjusted crop coefficients ($K_{c_{adj}}$) in deficit irrigation, derived not only as function of soil and climatic conditions and agronomic practices (Allen *et al.*, 1998; Myburgh, 2016), but also as function of genotype, phenological stage, differences between canopy size, row orientation, training system, vine spacing and different levels of soil water or salinity stress or specific floor management practices (*e.g.* surface

mulching or the use of cover crops), will enable an accurate determination of the adjusted (or actual) crop evapotranspiration ($ET_{c_{adj}}$) (see Allen and Pereira, 2009 and Pereira *et al.*, 2015 for a detailed general review). Also, the use of the “dual” K_c approach, that splits the K_c into the algebraic sum of a basal crop coefficient (K_{cb}) and a soil evaporation coefficient (K_e), and allows to separately account the contribution of soil evaporation (E) and grapevine (and cover crops, when present) transpiration (T) to the actual ET_c (Allen *et al.*, 2005; Farahani *et al.*, 2007; Fandiño *et al.*, 2012; Cancela *et al.*, 2015; Ferreira *et al.*, 2017), should be envisaged in order to better manage irrigation with water savings and decreased leaching risks. In fact, soil management practices (*e.g.* mulching) can minimize soil evaporation and help to control excessive soil temperatures (Dalmago, 2004) and promote soil fertility and water infiltration (Keller, 2015; Medrano *et al.*, 2015). Moreover, the use of low competition species and adequate management of cover crops, together with installation of water basins to retain winter’s rainwater, can promote water infiltration and increase water availability during summer period. Flowmeters in different sectors of the vineyard can help to quantify water use and improve water inputs’ inventory. Breeding and selection of varieties, clones and rootstocks with higher resistance to water and heat stress can also contribute to water savings (Gonçalves and Martins, 2012; Keller, 2015; Carvalho *et al.*, 2019), though this is a typical medium to long-term strategy.

Meanwhile, another very important component for sustainable water use in wine production is the precise application of PPP, as well as the management of related WW_{ppp} . Several techniques can reduce spray drift pollution from pesticide spraying in agricultural systems, as explained by Otto *et al.* (2015). A 38% reduction in drift pollution (*e.g.* using low-drift nozzles), up to a maximum of 98% reduction could be achieved if hedgerows co-occur alongside fields (EU Commission, 2016). The use of low or anti-drift equipment and techniques are thus recommended to be included in environmental regulatory programmes on a regional scale (OECD, 2014; Otto *et al.*, 2015). In addition, more precise knowledge on vineyard canopy architecture (height, width, volume, density and exposed leaf area) can help to optimize PPP and fertilizer treatments (Rosell and Sanz, 2012; Gil *et al.*, 2014). The wider use of wastewater collection infrastructures in the vineyard or evaporation of water from remnants in dehydration systems (Doruchowski *et al.*, 2014) will also help to minimize WW pollution.

Strategies for the winery

Monitoring plan for winery wastewaters

Water use in the winery represents the smallest part of water inputs for wine production, considering production of grapes under irrigated conditions. However, WW_{winery} production can have a major environmental impact (Christ and Burritt, 2013). The first step consists in a self-assessment program to compile existing data on water use, water quality, WW_{winery} sources and respective physical-chemical quality. This will help to identify hotspots and report gaps to prepare further assessment. It will also open the possibility to hierarchize winery operations in terms of water needs, contribution for WW_{winery} flows and organic loads. The monitoring plan should account the specific activities of Period I and Period II. The WW_{winery} treatment solutions should be adapted to fluctuations of volumes and loads, allowing an efficient removal of contaminants during the peak season. Because the organic matter content present in WW_{winery} is highly soluble and biodegradable, mainly during Period I, biological treatment systems are technically possible for this type of WW_{winery} (Oliveira *et al.*, 2009; Mosse *et al.*, 2011; Da Ros *et al.*, 2016). Development and use of effective and cheaper alternatives for WW_{winery} treatment is crucial to small/medium wineries to accomplish legal requirements for recycling or disposal (GWRDC, 2011). Cost-effective options for WW_{winery} recycling/disposal must rely on higher energy efficiency and low maintenance costs (Mosse *et al.*, 2011; Oliveira and Duarte, 2015; Kyzas *et al.*, 2016).

Winery wastewater recycling/disposal

In order to reduce costs with WW_{winery} recycling, there are some strategies to be implemented. For example, if the ultimate aim is to reuse treated WW_{winery} for irrigation purposes, domestic WW should not be combined with WW_{winery}. This will prevent contamination by bacteria, viruses and parasites, which require further treatments and a disinfection step. Moreover, the guidelines available for WW_{winery} reuse, in Old World Viticulture countries, include mainly microbiological parameters (Brissaud, 2008; Oliveira and Duarte, 2016). Regarding WW_{winery}, inorganic parameters are of particular concern; the sodium adsorption rate (SAR) is recommended to be below $6 \text{ mmol}^{1/2} \text{ L}^{-1/2}$, to prevent adverse soil structural changes (Laurenson *et al.*, 2010). To reduce SAR, some strategies should be applied in the winery (Kumar and Christen, 2009; Mosse *et al.*, 2011), namely the reuse of washing

water. The use of alternative cleaning agents based on potassium hydroxide and magnesium hydroxide, although more expensive, may be an option. The ozone treatment as a disinfection procedure will allow the decrease of the conductivity and COD, thus contributing to attain the compliance of the legal limits for uses in crop irrigation (Lucas *et al.*, 2009; Cullen and Norton, 2012). The reduction of COD can also be achieved by screening out solids larger than 0.5-1.0 mm with basket screens and by reducing the contact period between solids and WW, minimizing mass transfer. The replacement of citric acid by phosphoric acid is also an advantage (Brissaud, 2008). According to the World Health Organization recommendations for WW reuse (WHO, 2006), the amount of organic matter to be applied via irrigation should not exceed 500 mg L^{-1} , expressed as BOD₅, to avoid changes in soil properties (EPA, 2004). The same source states that application of an urban WW containing a BOD₅ between $110\text{--}400 \text{ mg L}^{-1}$ may be beneficial for crops (WHO, 2006). However, countries with more restrictive legislation only allow the use of WW with $20\text{--}30 \text{ mg L}^{-1}$ of organic matter expressed as BOD₅ (Tsagarakis *et al.*, 2004; Brissaud, 2008). Recent Portuguese legislation sets maximum values of $10\text{--}40 \text{ mg L}^{-1}$, expressed as BOD₅, for wastewater reuse in crop irrigation, according to quality classes (DL 119/2019). Also, the physical-chemical analysis could be insufficient to evaluate the potential ecological risk, since it does not allow the assessment of possible combined effects of different contaminants mixed together, as well as their bioavailability. Therefore, bioassays are recommended for ecological risk assessment of WW relative to soil or other matrices, whenever WW should be used as an organic amendment (Oliveira *et al.*, 2009; Mosse *et al.*, 2011).

Integrative strategies for a more sustainable wine production chain

The wine industry needs improved water metrics and integrative management strategies related to water fluxes in the vineyard and in the winery. To deal with water scarcity in the Mediterranean region, rain harvesting can be considered, furthering the water supply to the vineyard (Stec and Zelenáková, 2019). In addition, a conceptual overview of the existing water and WW flows along the wine production chain (vineyard and winery phases) should be envisaged, considering the “Farm-Winery” scenario, which is typical in regions such as Alentejo (Figure 3). Two distinct WW treatment approaches are proposed: the first relates to vineyard’s WW (WW_{ppp}) generated by the activities (*e.g.* crop protection) taking place in the

vineyard, whereas the second is related to WW_{winery} (Figure 3). Consequently, we consider two WW treatment plants in this analytical approach: an

agrochemical dedicated WW treatment plant (AWWTP) and an industrial WW treatment plant (IWWTP) (Figure 3).




Figure 3. "Farm-Winery" conceptual approach to improve vineyard and winery environmental management of water inputs and generated wastewater (WW) in the vineyard (WW_{PPP}) and in the winery (WW_{winery}). **Black arrows** indicate raw material and final product. **Blue arrows** indicate fresh water flows and **green arrows** represent WW_{winery} with different quality levels (Level 1 – improved quality & Level 2 – low quality). The **orange arrows** represent WW_{PPP} flows and the dark grey dotted lines are WW flows. **AWWTP** – Agrochemical dedicated WW_{PPP} Treatment Plant; **IWWTP** – Industrial WW_{winery} Treatment Plant.

*Abordagem conceptual do tipo "Farm-Winery" para melhor gestão ambiental da vinha e da adega em termos da origem do recurso água e das águas residuais geradas (WW), na vinha (WW_{PPP}) e na adega (WW_{winery}). As setas a cor negra indicam matéria-prima e produto final, enquanto as setas a azul indicam os fluxos de água doce do recurso água (input). As setas verdes representam WW com diferentes níveis de qualidade (Nível 1 - qualidade melhorada e Nível 2 - qualidade baixa). As setas a laranja representam água residual tratada com origem em pesticidas e seu uso (WW_{PPP}) e as linhas a tracejado e cinza escuro representam fluxos de WW. **AWWTP** – Estação de tratamento de agroquímicos dedicada a águas residuais; **IWWTP** – estação de tratamento industrial de águas residuais.*

Optimal water management in the winery must identify flows and loads as part of the working Periods I and II, as well as be a function of the type of grape processed (red vs. white grapes). This allows for segregation of flows and selection of the most biodegradable in order to improve WW_{winery} quality (Level 1 quality), which can be recycled within the winery, namely to wash the floors. In parallel, low quality water flows (e.g. with lower biodegradability and high polyphenol content) (Level 2 quality) are suggested to be used after being treated, to irrigate landscape crops surrounding the wineries or the vineyard, or as a small additional supply to vineyard's irrigation. Rain harvesting is another option to consider for reducing water consumption in wineries. It's worth noting that such decisions do require a previous cost-benefit analysis in order to ensure the economic viability and potential new projects.

More integrative approaches to optimize the implementation of climate change adaptation measures in viticulture and to optimize water use in the wine production chain should consider closer interaction and information exchange between all stakeholders (growers, winery managers, technical advisors, local and regional institutions, as well as government entities). A more efficient water management will be achieved when water metrics accommodate data from vineyards, up to the whole region and related governance.

CONCLUSIONS AND FUTURE PROSPECTS

Water must be protected and efficiently used, especially in dry areas. This paper provides a resumed overview and discussion over the water use and WW management in viticulture and oenology in South

Portugal. This review helps to clarify and emphasize existing limitations concerning water issues (e.g. efficiency, metrics) in wine production in dry regions and suggests possible approaches to optimize water and WW management in vineyards and wineries.

The typical inter-annual climate variability of Mediterranean climates and more extreme climate events offer increasing challenges when estimating water needs and water use in irrigated vineyards. Indeed, water consumption can be highly variable in the field (due to climate conditions), but also in the winery. In this case, the size of the winery, the type of wine produced and the winemaking periods (I and II) are important variation factors.

Simple water and WW indicators to be used in vineyards and wineries were highlighted and should contribute to: 1) optimize water and WW management in irrigated vineyards in dry areas such as Alentejo (Portugal); 2) optimize water and WW management in the winery; 3) support improved water management in accordance to the specificities of the wine production chain, and ultimately 4) minimize the potential environmental impact of the wine industry. Future studies should test the potential combination of water stress/water scarcity indicators

with other analysis tools (e.g. WFP and LCA) to support the wine industry in assessing its environmental impact at farm and regional levels. Indicators such as Carbon Footprint or Ecological Footprint should complement studies focused on water use and WW production in the wine sector. Sustainability and certification programs must consider the water component in both the vineyard and winery, especially in dry areas. These initiatives improve stakeholders' perception of sustainability issues and sustainability certification, which require robust water metrics and data reporting. Still, analysis of medium to long-term impacts of WW on crop and soil needs more detailed studies, particularly for wine production under dry and warm climates.

ACKNOWLEDGMENTS

We thank to Fundação para a Ciência e Tecnologia (Portugal) through the research unit UID/AGR/04129/2013 (LEAF). J. M. Costa and Carlos Lopes also acknowledge the support of the EU project NEFERTITI (EU Horizon 2020, grant agreement No. 772705), Network 8 – Water Use Efficiency.

REFERENCES

- Allen R.G., Pereira L.S., 2009. Estimating crop coefficients from fraction of ground cover and height. *Irrig. Sci.*, **28**, 17-34.
- Allen R.G., Pereira L.S., Smith M., Raes D., Wright J.L., 2005. FAO-56 Dual crop coefficient method for estimating evaporation from soil and application extensions. *J. Irrig. Drain. Eng.*, **131**, 2-13.
- Amienyo D., Camilleri C., Azapagic A., 2014. Environmental impacts of consumption of Australian red wine in the UK. *J. Clean. Prod.*, **72**, 110-119.
- Andreattola G., Foladori P., Ziglio G., 2009. Biological treatment of winery wastewater: an overview. *Water Sci. Technol.*, **60**, 1117-1125.
- Barroso J.M., Pombeiro L., Rato A.E., 2017. Impacts of crop level, soil and irrigation management in grape berries of cv 'Trincadeira' (*Vitis vinifera* L.). *J. Wine Res.*, **28**, 1.
- Bolzonella D., Fatone F., Pavan P., Cecchi F., 2010. Application of a membrane bioreactor for winery wastewater treatment. *Water Sci. Technol.*, **62**, 2754-2759.
- Bonamente E., Scrucca F., Asdrubali F., Cotana F., Presciutti A., 2015. The water footprint of the wine industry: Implementation of an assessment methodology and application to a case study. *Sustainability*, **7**, 12190-12208.
- Brissaud F., 2008. Criteria for water recycling and reuse in the Mediterranean countries. *Desalination*, **218**, 24-33.
- Brown I., Poggio L., Gimona A., Castellazzi M., 2011. Climate change, drought risk and land capability for agriculture: implications for land use in Scotland. *Reg. Environ. Change*, **11**, 503-518.
- Campos J., Llop J., Gallart M., García-Ruiz F., Gras A., Salcedo R., Gil E., 2019. Development of canopy vigour maps using UAV for site-specific management during vineyard spraying process. *Prec. Agric.*, 1-21.
- Cancela J.J., Fandiño M., Rey B.J., Martínez E.M., 2015. Automatic irrigation system based on dual crop coefficient, soil and plant water status for *Vitis vinifera* (cv Godello and cv Mencía). *Agric. Water Man.*, **151**, 52-63.
- Capri E., 2016. Footprinting the sustainable wine production in Italy. Available online: http://www.viticolturasostenibile.org/Downloads/Setac_2016.pdf.
- Carvalho L., Gonçalves E., Amâncio S., Martins A., 2019. Polyclonal selection to improve tolerance to abiotic stress. *Livro de Actas Simpósio de Vitivinicultura do Alentejo 2019*, pp. 35-44.
- Castex V., Moran-Tejeda E., Beniston M., 2015. Water availability, use and governance in the wine producing region of Mendoza, Argentina. *Environ. Sci. Policy*, **48**, 1-8.
- Chaves M.M., Zarrouk O., Francisco R., Costa J.M., Santos T., Regalado A.P., Rodrigues M.L., Lopes C.M., 2010. Grapevine under deficit irrigation: hints from physiological and molecular data. *Ann. Bot.*, **105**, 661-676.
- Chiusano L., Cerutti A.K., Cravero M.C., Bruun S., Gerbi V., 2015. An industrial ecology approach to solve wine surpluses problem: the case study of an Italian winery. *J. Clean. Prod.*, **91**, 56-63.
- Christ K.L., Burritt R.L., 2013. Critical environmental concerns in wine production: an integrative review. *J. Clean. Prod.*, **53**, 232-242.
- Comandaru I., Bârjoveanu G., Peiu N., Ene S., Teodosiu C., 2012. Life cycle assessment of wine: focus on water use impact assessment. *Environ. Eng. Man. J.*, **11**, 533-543.

- Corbo C., Lamastra L., Capri E., 2014. From environmental to sustainability programs: a review of sustainability initiatives in the Italian wine sector. *Sustainability*, **6**, 2133-2159.
- Correia A. 2015. *A Vitivinicultura na região do Alentejo: A passagem de um setor tradicional para um setor inovador O caso da sub-região vitivinícola de Reguengos de Monsaraz*. Dissertação de Mestrado em Gestão do Território – área de especialização em Planeamento e Ordenamento do Território. Universidade Nova de Lisboa. 124pp.
- Costa J.M., Vaz M., Escalona J., Egipto R., Lopes C., Medrano H., Chaves M.M., 2016. Modern viticulture in southern Europe: Vulnerabilities and strategies for adaptation to water scarcity. *Agric. Water Man.*, **164**, 5-18.
- Costa J.M., Oliveira M., Egipto R., Fragoso R., Lopes C., Duarte E., 2019. Gestão da água para uma viticultura sustentável no sul de Portugal. *Livro de Actas Simpósio de Vitivinicultura do Alentejo* 2019, p. 289-297.
- COTR-ATEVA, 2009. Benchmarking na rega e boas práticas na gestão da rega da vinha. Eds. Centro Operativo e de Tecnologia do Regadio, Associação Técnica dos Viticultores do Alentejo. Available online: https://www.ateva.pt/ateva_site_media/cms_page_media/58/Boas%20Praticas%20de%20gest%C3%A3o%20da%20Rega%20da%20Vinha.pdf.
- CSWA 2014. *Certified California sustainable winegrowing: certification guidebook*. Lloyd's Register Quality Assurance (LRQA); PE INTERNATIONAL, Inc. & Five Winds Strategic Consulting Eds, San Francisco, USA. 149 pp.
- Cullen P.J., Norton T., 2012. Ozone Sanitisation in the Food Industry. In: *Ozone in Food Processing*. C. O'Donnell, B.K. Tiwari, P.J. Cullen and R.G. Rice (Eds.), Wiley-Blackwell, Oxford, UK.
- CVRA, 2002. A rega da vinha no Alentejo. Comissão Vitivinícola Regional Alentejana, 2016. Available online: http://sapecagro.pt/download/A_rega_da_Vinha_no_Alentejo.pdf.
- CVRA, 2016. Facts and Figures. Comissão Vitivinícola Regional Alentejana, 2016. Available online: http://www.vinhosdoalentejo.pt/media/cvra/Alentejo_Wines_-_Facts_Figures_Fev2016_Ing.pdf.
- Dalmago G.A., 2004. Dinâmica da água no solo em cultivos de milho sob plantio direto e preparo convencional. , UFRGS, Porto Alegre, Brasil, 245pp.
- Da Ros, C., Cavinato C., Pavan P., Bolzonella D., 2016. Mesophilic and Thermophilic Anaerobic Co-Digestion of Winery Wastewater Sludge and Wine Lees: An Integrated Approach for Sustainable Wine Production. *J. Environ. Man.*, **203**, 745-752. doi: 10.1016/j.jenvman.2016.03.029.
- DL 119/2019, de 21 de agosto. Estabelece o regime jurídico de produção de água para reutilização, obtida a partir do tratamento de águas residuais, bem como da sua utilização. <https://dre.pt/application/conteudo/124097549>.
- Devesa-Rey R., Vecino X., Varela-Alende J.L., Barral M.T., Cruz J.M., Moldes A.B., 2011. Valorization of winery waste vs. the costs of not recycling. *Waste Man.*, **31**, 2327-2335.
- Doruchowski G., Balsari P., Gil E., Marucco P., Roettele M., Wehmann H.J., 2014. Environmentally Optimised Sprayer (EOS) - a software application for comprehensive assessment of environmental safety features of sprayers. *Sci. Total Environ.*, **483**, 201-207.
- Duarte E.A., Reis I.B., Martins M.O., 2004. Implementation of an environmental management plan towards the global quality concept – A challenge to the winery sector. In: *Proceedings of the 3rd International Specialised Conference on Sustainable Viticulture and Winery Wastes Management*, University of Barcelona, Barcelona, Spain, 23-30.
- EDIA, 2018. Anuário Agrícola de Alqueva. Direção de Economia da Água e Apoio ao Cliente - Departamento de Economia da Água, Beja. Available online: https://www.edia.pt/wp-content/uploads/2019/05/anuario_agricola-alqueva_2018.pdf
- EIP-AGRI, 2019. EIP-AGRI Focus Group Diseases and pests in viticulture, FINAL REPORT, MARCH 2019. Available online: https://ec.europa.eu/eip/agriculture/sites/agri-eip/files/eip-agri_fg_diseases_and_pests_in_viticulture_final_report_2019_en.pdf.
- Ene S.A., Teodosiu C., Robu B., Volf I., 2013. Water footprint assessment in the winemaking industry: a case study for a Romanian medium size production plant. *J. Clean. Prod.*, **43**, 122-135.
- Engel M., Hörnlein T., Jacques F., Ohlsson A., 2015. *Manual de produção mais limpa para adegas*. Comissão Vitivinícola Regional Alentejana & International Institute for Industrial Environmental Economics. 43pp.,
- EPA, 2004. Guidelines for Wineries and Distilleries. 20 p., Environmental Protection Authority, Adelaide, Australia. Available online: http://www.epa.sa.gov.au/xstdfiles/Industry/Guideline/guide_wine_ries.pdf.
- EU Commission, 2012. Gap analysis of the water scarcity and droughts policy in the EU, European Commission Tender ENV.D.1/SER/2010/0049, August 2012. Available online: <http://ec.europa.eu/environment/water/quantity/pdf/WSDGapAnalysis.pdf>.
- EU Commission 2016. *Techniques to reduce spray drift pollution from vineyards*. Available online: https://ec.europa.eu/environment/integration/research/newsalert/pdf/techniques_to_reduce_spray_drift_pollution_from_vineyards_433n1_en.pdf.
- EU Commission, 2017. *Characterization of unplanned water reuse in the EU. Final report*. October 2017. Available online: http://ec.europa.eu/environment/water/pdf/Report-UnplannedReuse_TUM_FINAL_Oct-2017.pdf.
- Esporão, 2018. *Guia da colheita 2017 - Guia de bolso*. Available online: https://www.esporao.com/wp-content/uploads/2018/12/Guia_de_Colheita_2017_.pdf.
- Eusébio A, Mateus M, Baeta-Hall L, Almeida-Vara E, Duarte J, 2005. Microflora evaluation of two agro-industrial effluents treated by the JACTO jet-loop type reactor system. *Water Sci. Technol.*, **51**, 107-112.
- Fandiño M., Cancela J.J., Rey B.J., Martínez E.M., Rosa R.G., Pereira L.S., 2012. Using the dual-Kc approach to model evapotranspiration of Albariño vineyards (*Vitis vinifera* L. cv. Albariño) with consideration of active ground cover. *Agric. Water Man.*, **112**, 75-87.
- Farahani H.J., Howell T.A., Shuttleworth W.J., Bausch W.C., 2007. Evapotranspiration: Progress in measurement and modeling in agriculture. *Transactions ASABE*, **50**, 1627-1638.
- Ferreira M.I., Conceição N., Malheiro A.C., Silvestre J.M., Silva R.M., 2017. Water stress indicators and stress functions to calculate soil water depletion in deficit irrigated grapevine and kiwi. *Acta Hort.*, **1150**, 119-126.
- Fernández B, Seijo I, Ruiz-Filippi G, Roca E, Tarenzi L, Lema JM, 2007. Characterization, management and treatment of wastewater from white wine production. *Water Sci. Technol.*, **56**, 121-128.

- Fraga H, García de Cortázar Atauri I, Santos J, 2018. Viticultural irrigation demands under climate change scenarios in Portugal. *Agric. Water Man.*, **196**, 66-74.
- Gil E., Arnó J., Llorens J., Sanz R., Llop J., Rosell-Polo J.R., Gallart M., Escolà A., 2014. Advanced technologies for the improvement of spray application techniques in Spanish viticulture: An overview. *Sensors*, **14**, 691-708.
- Gil E., Llorens J., Landers A., Llop J., Giralt L., 2011. Field validation of dosaviña, a decision support system to determine the optimal volume rate for pesticide application in vineyards. *Eur. J. of Agron.*, **35**, 33-46.
- Gonçalves E., Martins A., 2012. Genetic variability evaluation and selection in ancient grapevine varieties. In: **Plant Breeding**. Abdurakhmonov, I.Y. (ed.). IntechOpen, 333-352.
- GWRDC, 2011. *Winery wastewater management and recycling - operational guidelines*. 79 p., Grape and Wine Research and Development Corporation. Adelaide, Australia. Available online: <https://www.wineaustralia.com/getmedia/72627da6-d28a-42f2-b600-28fdd5a6c85c/Operational-Guidelines.pdf>.
- Hoekstra A.Y., Chapagain A.K., Aldaya M.M., Mekonnen M.M., 2011. *The water footprint assessment manual: Setting the global standard*. 228 p., Earthscan, London, UK.
- IFV, 2010. *Euroviti. Compte Rendu. Effluents phytosanitaires: s'organiser sur son exploitation pour les gérer et les traiter effluents phytosanitaire :s'organiser sur son exploitation pour les gérer et les traiter*. Institut Français de la Vigne et du Vin <https://www.vignevin.com/wp-content/uploads/2019/03/Itineraires-22-BD.pdf>
- Iglesias A., Garrote L., 2015. Adaptation strategies for agricultural water management under climate change in Europe. *Agric. Water Man.*, **155**, 113-124.
- IPMA, 2017. Instituto Português do Clima e Atmosfera. Available online: <https://www.ipma.pt/pt/educativa/tempo.clima/index.jsp?pa ge=clima.pt.xml>.
- INE, 2013. *Inquérito à estrutura das explorações agrícolas 2013*. Instituto Nacional de Estatística, I. P., Lisboa.
- INE, 2016. *Inquérito à estrutura das explorações agrícolas 2016*. Instituto Nacional de Estatística, I. P., Lisboa.
- ISO, 2014. ISO & water: global solutions to global challenges. Available online: http://www.iso.org/iso/iso_and_water.pdf.
- IVV, 2016. *Anuário de Vinhos e Aguardentes de Portugal 2016*. Instituto da Vinha e do Vinho, Lisboa.
- IVV, 2018. *Anuário de vinhos e aguardentes de Portugal 2018*. Instituto da Vinha e do Vinho, Lisboa.
- Keller M., 2015. Managing grapevines to optimize fruit development in a challenging environment: a climate change primer for viticulturists. In: *Environmentally Sustainable Viticulture, Practices and Practicality*. Gerling C. (ed.), Apple Academic Press, 259-292.
- Kuflik T., Prodorutti D., Frizzi A., Gafni Y., Simon S., Pertot I., 2009. Optimization of copper treatments in organic viticulture by using a web-based decision support system. *Comput. Electron. Agric.*, **68**, 36-43.
- Kumar A., Kookana R., 2006. *Impact of winery wastewater on ecosystem health. An introductory assessment. Final report*. GWRDC. CSL 02/03. 139.
- Kumar A., Christen E., 2009. *Developing a systematic approach to winery wastewater management. Final Report to the GWRDC*. Project Number: CSL05/02, CSIRO Land and Water Science Report Adelaide, 31 pp.
- Kyzas G.Z., Symeonidou M.P., Matis K.A., 2016. Technologies of winery wastewater treatment: a critical approach. *Desalination Water Treat.*, **57**, 1-15.
- Lamastra L., Suciú N.A., Novelli E., Trevisan M., 2014. A new approach to assessing the water footprint of wine: an Italian case study. *Sci. Total Environ.*, **490**, 748-756.
- Laurenson S., Bolan N., Smith E., McCarthy M., 2010. *Winery wastewater irrigation: Effects of potassium and sodium on soil structure*. CRC CARE Technical Report no. 19, CRC for Contamination Assessment and Remediation of the Environment, Adelaide, Australia.
- Levidow, L., Zaccaria, D., Maia, R., Vivas, E., Todorovic, M., & Scardigno, A., 2014. Improving water-efficient irrigation: Prospects and difficulties of innovative practices. *Agric. Water Man.*, **146**, 84-94. doi: 10.1016/j.agwat.2014.07.012.
- Liu J., Yang H., Gosling S.N., Kumm M., Flörke M., Pfister S., Hanasaki N., Wada Y., Zhang X., Zheng C., Alcamo J., Oki T., 2017. Water scarcity assessments in the past, present and future. *Earth's Future*, **5**, 545-559.
- Lofrano G., Belgiorio V., Mascolo A., 2009. Winery wastewater treatment options: drawbacks and advantages. In: *Proceedings of the 5th Int. Spec. Conf. on Sust. Vitic.: Winery Wastes and Ecol. Impacts Manag.* University of Trento, Trento and Verona, Italy, 27-34.
- Lopes C.M., Costa J.M., Egipto R., Zarrouk O., Chaves M.M., 2018. Can Mediterranean terroirs withstand climate change? Case studies at the Alentejo Portuguese winegrowing region. *E3S Web of Conferences*, **50**, 01004.
- Lovarelli D., Bacenetti J., Fiala M., 2016. A new tool for life cycle inventories of agricultural machinery operations. *J. Agric. Eng.*, **47**, 40-52.
- Lucas M.S., Peres J.A., Lan B.Y., Puma G.L., 2009. Ozonation kinetics of winery wastewater in a pilot-scale bubble column reactor. *Water Res.*, **43**, 1523-1532
- Lucas M.S., Peres J.A., Li Puma G., 2010. Treatment of winery wastewater by ozone-based advanced oxidation processes (O3, O3/UV and O3/UV/H2O2) in a pilot-scale bubble column reactor and process economics. *Sep. Purif. Technol.*, **72**, 235-241.
- Myburgh P.A., 2016. Estimating transpiration of whole grapevines under field conditions. *S. Afr. J. Enol. Vitic.*, **37**, 47-60.
- Martins A.A., Araújo A.R., Graça A., Caetano N.S., Mata T.M., 2018. Towards sustainable wine: comparison of two Portuguese wines. *J. Clean Prod.*, **183**, 662-676.
- Medrano H., Tomás M., Martorell S., Flexas J., Hernández E., Rosselló J., Pou A., Escalona J.M., Bota J., 2015. From leaf to whole-plant water use efficiency (WUE) in complex canopies: limitations of leaf WUE as a selection target. *The Crop J.*, **3**, 220-228.
- Moore B.C., Coleman A.M., Wigmosta M.S., Skaggs R.L. and Venteris E.R., 2015. A high spatiotemporal assessment of consumptive water use and water scarcity in the conterminous United States. *Water Resour. Manag.*, **29**, 5185-200.
- Mosse K.P.M., Patti A.F., Christen E.W., Cavagnaro T.R., 2011. Review: Winery wastewater quality and treatment options in Australia. *Aust. J. Grape Wine Res.*, **17**, 111-122.
- Neto B., Dias A.C., Machado M., 2013. Life cycle assessment of the supply chain of a Portuguese wine: from viticulture to distribution. *Int. J. Life Cycle Assess.*, **18**, 590-602.

- OECD, 2011. *Water governance in OECD countries: A multi-level approach*. OECD Studies on Water, OECD Publishing.
- OECD, 2014. *Enhanced efficacy, efficiency and safety through improved application*. Available online: <http://www.oecd.org/chemicalsafety/pesticides-biocides/37237992.pdf>.
- OIV, 2018. *State of the vitiviniculture world market - April 2018*. Available online: <http://www.oiv.int/public/medias/5958/oiv-state-of-the-vitiviniculture-world-market-april-2018.pdf>.
- Okada D.Y., Delforno T.P., Esteves A.S., Sakamoto I.K., Duarte I.C.S., Varesche M.B.A., 2013. Optimization of linear alkylbenzene sulfonate (LAS) degradation in UASB reactors by varying bioavailability of LAS, hydraulic retention time and specific organic load rate. *Bioresource Technol.*, **128**, 125-133.
- Oliveira M., Costa J.M., Fragoso R., Duarte E., 2019. Challenges for modern wine production in dry areas: dedicated indicators to preview wastewater flows. *Water Supply*, **19**, 653-661.
- Oliveira M., Duarte E., 2015. Winery wastewater treatment: Evaluation of the air micro-bubble bioreactor performance. Towards a sustainable wine industry. *Toward a Sustainable Wine Industry: Green Enology Research*, Chapter 4, pp. 79-113. Preston-Wilsey Eds, 1st Edition, CRC Press, Canada.
- Oliveira M., Duarte E., 2016. Integrated approach to winery waste: waste generation and data consolidation. *Front. Environ. Sci. Eng.*, **10**, 168-176.
- Oliveira M., Queda C., Duarte E., 2009. Aerobic treatment of winery wastewater with the aim of water reuse. *Water Sci. Technol.*, **60**, 1217-1223.
- Oliveira M., Costa J.M., Fragoso R., Duarte E., 2019. Challenges for modern wine production in dry areas: dedicated indicators to preview wastewater flows. *Water Sci. Technol.: Water Supply*, **19**, 653-661.
- Otto S., Loddo D., Baldoin C., Zanin G., 2015. Spray drift reduction techniques for vineyards in fragmented landscapes. *J. Environ. Manage.*, **162**, 290.
- Peel M.C., Finlayson B.L., McMahon T.A., 2007. Updated world map of the Köppen-Geiger climate classification. *Hydrol. Earth Syst. Sci.*, **11**(5), 1633-1644.
- Pereira L.S., Allen R.G., Smith M., Raes D., 2015. Crop evapotranspiration estimation with FAO56: Past and future. *Agric. Water Man.*, **147**, 4-20.
- Pérez-Expósito J.P., Fernández-Caramés T.M., Fraga-Lamas P., Castedo L., 2017. VineSens: An eco-smart decision-support viticulture system. *Sensors*, **17**, 465.
- Perry C., 2014. Water footprints: Path to enlightenment, or false trail? *Agric. Water Man.*, **134**: 119-125.
- Peth D., Drastig K., Prochnow A., 2017. Quantity- and quality-based farm water productivity in wine production: Case studies in Germany. *Water*, **88**, 1-14.
- Petrucchioli M., Duarte J.C., Eusebio A., Federici F., 2002. Aerobic treatment of winery wastewater using a jet-loop activated sludge reactor. *Process Biochem.*, **37**, 821-829.
- Pfister S., Koehler A., Hellweg S., 2009. Assessing the environmental impacts of freshwater consumption in LCA. *Environ. Sci. Technol.*, **43**, 4098-4104.
- Pfister S., Bayer B., 2014. Monthly water stress: spatially and temporally explicit consumptive water footprint of global crop production. *J. Clean. Prod.*, **73**, 52-62.
- Pfister S., Boulay A.M., Berger M., Hadjikakou M., Motoshita M., 2017. Understanding the LCA and ISO water footprint: A response to Hoekstra 2016. A critique on the water-scarcity weighted water footprint in LCA. *Ecol. Indic.*, **72**, 352-359.
- Pirra A., Bianchi A. 2007. A poluição provocada pelo sector vitivinícola", *Rev. Associação Portuguesa de Horticultura*, **89**, 25-28.
- Quinteiro P., Dias A.C., Pina L., Neto B., Ridoutt B.G., Arroja L., 2014. Addressing the freshwater use of a Portuguese wine ('vinho verde') using different LCA methods. *J. Clean. Prod.*, **68**, 46-55.
- Radke J., Pinto P., Lachhwani K., Kondolf G.M., Rocha J., Lobet A.S., Edwards D., Francella V., Jurich K., McKnight K., Alex R.A., Eng T., Harrell B., Uennatomwarangoon F., Wolfson E., Alfaro P.J., Ding E., Marzion R., 2015. *Alqueva changing ecologies of the montado landscape, Alentejo, Portugal*. Available online: <http://ced.berkeley.edu/downloads/research/AlquevaReportLA205-2015.pdf>.
- Riou C., Carbonneau A., Becker N., Calo' A., Costacurta A., Castro R., Pinto P.A., Carneiro L.C., Lopes C., Climaco P., Panagiotou M.M., Sotéz V., Beaumont H.C., Burril A., Maes J., Vossen P., 1994. *Le déterminisme climatique de la maturation du raisin: Application au zonage de la teneur en sucre dans la Communauté Européenne*. Office des Publications Officielles des Communautés Européennes, Luxembourg.
- Rochard J., Codis, S., 2004. *Gestion des eaux de lavage des pulvérisateurs*. Institut Français de la Vigne et du Vin, 8p.
- Rochard J., Kerner S., 2009. Innovation environnementale dans la gestion des effluents de cave: application des lits plantes de roseaux. *Rev. Oenol.* **133S**, **36**, 52-54.
- Román-Sánchez I.M., Aznar-Sánchez J.A., Belmonte-Ureña L.J., 2015. Heterogeneity of the environmental regulation in Europe. *Water Sci. Technol.*, **72**, 1667-1672.
- Rosell J.R., Sanz R.A., 2012. Review of methods and applications of the geometric characterization of tree crops in agricultural activities. *Comput. Electron. Agric.*, **81**, 124-141.
- Santiago-Brown I., Metcalfe A., Jerram C., Collins C., 2015. Sustainability assessment in wine-grape growing in the new world: Economic, environmental, and social indicators for agricultural businesses. *Sustainability*, **7**, 8178-8204.
- Santini C., Cavicchi A., Casini L., 2013. Sustainability in the wine industry: key questions and research trends. *Agric. Food Econ.*, **1**, 1-14.
- Saraiva, A.; Egipto, R.; Presumido P.; Jorge C.; Amaral A.; Castro Ribeiro A.; Dias I.; Feliciano M.; Ferreira A.; Ferreira L.; Gonçalves A.; Grifo A.; Mamede H.; Mira H.; Oliveira A.; Oliveira E Silva P.; Paulo A.; Ribeiro A.; Rodrigues G.; Silvestre J.; Ramôa S.; Oliveira M. 2019. Determinação da pegada hídrica na fileira vitivinícola: resultados preliminares de um estudo de caso português. *Livro de Actas Simpósio de Vitivinicultura do Alentejo* 2019, pp.155-162.
- Shepherd H.L., Grismer M.E., Tchobanoglous G., 2001. Treatment of high-strength winery wastewater using a subsurface flow constructed wetland. *Water Environ. Res.*, **73**, 597-606.
- Silvestre J., Damásio M., Egipto R., Cunha J., Brazão J., Eiras-Dias J. Flores R., Rodrigues A., Donno P., Böhm J., 2018. Tolerância ao escaldão na vinha: uma variável a considerar num contexto de alterações climáticas. *Vida Rural*, **1842**, 38-42.
- Skewes M., 1998. *Irrigation benchmarking for winegrapes*. Aust. Grape .Wine., 61-64 Skewes M., Meissner A.P., 1997. Irrigation

- benchmarks and best management practices for winegrapes. Primary Industries and Resources SA. Technical Report.
- Stec A., Zelenáková M., 2019. An analysis of the effectiveness of two rainwater harvesting systems located in Central Eastern Europe. *Water*, **11**, 458, 1-16.
- Stephano N., Quayle W., Arienzo M., Zandona R., Blackwell B., Christen E., 2008. *A low cost land based winery wastewater treatment system: Development and preliminary results*. CSIRO Land and Water Science Report 43/08, Australia, 58 pp.
- Tsagarakis K.P., Dialynas G.E., Angelakis A.N., 2004. Water resources management in Crete (Greece) including water recycling and reuse and proposed quality criteria. *Agric. Water Man.*, **66**, 35-47.
- UN-WATER, 2015. *Climate change adaptation: The pivotal role of water*. Available online: http://www.unwater.org/downloads/unw_ccpol_web.pdf.
- van Schoor L.H., 2005. *Guidelines for the management of wastewater and soil waste at existing wineries*. Winetech Ed. South Africa, 35 pp.
- Vanham D., Bidoglio G., 2013. A review on the indicator water footprint for the EU28. *Ecol. Indic.*, **26**, 61-75.
- Vázquez-Rowe I., Villanueva-Rey P., Moreira M.T., Feijoo G., 2012. Environmental analysis of Ribeiro wine from a timeline perspective: Harvest year matters when reporting environmental impacts. *J. Environ. Manage.*, **98**, 73-83.
- Vlyssides A.G., Barampouti E.M., Mai S. 2005. Wastewater characteristics from Greek wineries and distilleries. *Water Sci. Technol.*, **51**, 53-60.
- Vörösmarty C.J., Green P., Salisbury J., Lammers R.B., 2000. Global water resources: vulnerability from climate change and population growth. *Science*, **289**, 284-288.
- Welz P.J., Holtman G., Haldenwang R., le Roes-Hill M. 2016. Characterization of winery wastewater from continuous flow settling basins and waste stabilization ponds over the course of 1 year: implications for biological wastewater treatment and land application. *Water Sci. Technol.*, **74**, 2036-2050.
- WHO, 2006. *WHO Guidelines for the safe use of wastewater, excreta, and greywater. Vol. IV Excreta and Greywater use in Agriculture*. 204 p., WHO, France.
- Xu H., Wu M., 2017. *Water availability indices – a literature review*. Argonne National Laboratory. February 2017. Available online: http://water.es.anl.gov/documents/Technical%20Report_%20Literature%20Review%20of%20Water%20Availability%20Indices_030317.ems_vs.pdf.
- Zhuo L., Mekonnen M.M., Hoekstra A.Y., Wada Y., 2016. Inter- and intra-annual variation of water footprint of crops and blue water scarcity in the Yellow River basin (1961–2009). *Adv. Water Res.*, **87**, 29-41.